



Carrier



PORTABLE 51QPD



- Compact design, ideal for small spaces too.
- **Versatile:** equipped with multi-directional rotors and a practical side handle for transport.
- The **intelligent on-off technology** allows the unit to activate energy saving automatically when in standby mode.
- Automatic condensation vaporisation in air conditioning mode.
- Possibility of continuous condensation discharge in dehumidifier mode.



UNIT		51QPD12N7S	
Power supply		V-Ph-Hz	220-240V,1Ph,50Hz
Cooling	Capacity	BTU/h	12000
	Capacity	kW	3.5
	Nominal power draw	W	1350
	Nominal current draw	A	5.9
	EER	W/W	2.6
	Energy Efficiency Class		A
Heating	Capacity	BTU/h	10000
	Capacity	kW	2.9
	Nominal power draw	W	1045
	Nominal current draw	A	5.0
	COP	W/W	2.8
	Energy Efficiency Class		A+
Dehumidifying capacity		L/h	3.25
Maximum power draw		W	1600
Maximum current draw		A	8.0
Energy consumption on activation		A	25
Air flow (Hi)		m³/h	420 / 370 / 350
Sound pressure level (Hi/Med/Lo)		dB(A)	55 / 54 / 53
Sound power level (Hi)		dB(A)	64
Energy consumption in thermostat mode turned off		W	1
Energy consumption in standby mode		W	0.5
Refrigerant	Type		R290
	GWP		3
	Additional refrigerant load	kg	0.23
	CO ₂ quantity	kg	0.69
Test pressure		MPa	2.6 / 1.0
Type of plug			1.5x3/VDE
Type of Control			Remote Control
Indoor temperature		°C	17-35 / 5-30
Space Area		m²	16-23
Dimensions (LxWxH)		mm	467×397×765
Package (LxWxH)		mm	515×440×890
Weight (net/gross)		Kg	34.4 / 37.8